

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANT: FITZGIBBON, Russell Patrick

SERIAL NO.: 10/705,681

FILED: November 12, 2003

TITLE: TOOL HOLDER ARRANGEMENT

TRANSMITTAL OF CERTIFIED COPY OF FOREIGN PRIORITY DOCUMENT

Commissioner for Patents
P. O. Box 1450
Alexandria, VA 22313-1450

Sir:

Attached please find the Foreign Priority Document, United Kingdom Patent Application No. 0301242.4 filed on 20 January 2003.

Respectfully submitted,

Date JAN 08 2004

John S. Egbert
Reg. No. 30,627
Harrison & Egbert
412 Main Street, 7th Floor
Houston, Texas 77002
(713)224-8080
(713)223-4873 (Fax)

CERTIFICATE OF MAILING UNDER 37 CFR 1.8(a)

I hereby certify that the attached CERTIFIED COPY OF FOREIGN PRIORITY DOCUMENT is being deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to:

Commissioner for Patents
P. O. Box 1450
Alexandria, VA 22313-1450

on JAN 08 2004 2004.

Date JAN 08 2004

John S. Egbert



INVESTOR IN PEOPLE


The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed 
Dated 22 October 2003



1/77

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference	NHF/ATB/cg		
2. Patent application number (The Patent Office will fill in this part)	20 JAN 2003	0301242.4	
3. Full name, address and postcode of the or of each applicant (underline all surnames)	Armstrong Healthcare Limited, Riverlock House, Spring Gardens Road, High Wycombe, HP13 7AG		
Patents ADP number (if you know it)	07103484002		
If the applicant is a corporate body, give the country/state of its incorporation	UNITED KINGDOM		
4. Title of the invention	A Tool Holder Arrangement		
5. Name of your agent (if you have one)	Forrester Ketley & Co.		
'Address for service' in the United Kingdom to which all correspondence should be sent (including the postcode)	Forrester House 52 Bounds Green Road London N11 2EY		
Patents ADP number (if you know it)	133001	✓	
6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number	Country	Priority application number (if you know it)	Date of filing (day / month / year)
7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application	Date of filing (day / month / year)	
8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if: a) any applicant named in part 3 is not an inventor, or b) there is an inventor who is not named as an applicant, or c) any named applicant is a corporate body. See note (d))	YES		

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form	-
Description	9
Claim(s)	4
Abstract	1
Drawing(s)	1 + 1. SW

10. If you are also filing any of the following, state how many against each item.

Priority documents	NONE
Translations of priority documents	-
Statement of inventorship and right to grant of a patent (Patents Form 7/77)	1
Request for preliminary examination and search (Patents Form 9/77)	-
Request for substantive examination (Patents Form 10/77)	-
Any other documents (please specify)	-

11. I/We request the grant of a patent on the basis of this application.

Signature Forrester Ketley & Co. Date

20th January, 2003

Forrester Ketley & Co.

12. Name and daytime telephone number of person to contact in the United Kingdom
FRANKLAND, Nigel H.
(020) 8889 6622

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Patents Form 1/77

DUPLICATE

PATENTS ACT 1977

P17091GB-NF/jsd/cg

5

“A TOOL HOLDER ARRANGEMENT”

THIS INVENTION relates to a tool holder arrangement, and in particular
10 concerns a tool holder arrangement incorporating a system for uniquely
identifying a surgical tool attached to a tool holder.

The use of medical robots has become widespread in recent years, in
particular for surgical procedures requiring a high degree of precision, for
15 instance minimal access or “keyhole” surgery.

Typically, a medical robot comprises an arm which is movable under
computer control, and to which any one of several different tools may be
attached. During the course of a surgical procedure, several different tools may
20 be required, and each will be attached in turn to the arm of the medical robot.

Because the tools must be sterile to qualify for use in surgical
procedures, conventional identification means such as labelling or marking may
not be available for the purpose of distinguishing between tools. In addition,
25 electrical safety and clinical practice requires that the patient is electrically
“floating”, that is, isolated from any power sources and not earthed. Hence,
when the tool contacts the patient during a surgical procedure, this contact must
not provide a ground path through which current could flow between the
patient and ground.

Because a medical robot is a safety-critical device, it is a requirement in most jurisdictions for medical robots to be immune from single-point failures. In other words, it is preferable for there to be two independent means for
5 verifying which tool is attached to the arm of the robot.

The present invention seeks to alleviate some or all of the above difficulties.

10 According to this invention there is provided a tool holder arrangement including: a tool holder to be mounted on a support and allowing removable attachment thereto of any one of a plurality of tools; a sensor arrangement operable to sense at least one feature present on a tool when attached to the tool holder, being a feature or features unique to the specific tool; and a processor
15 operable to identify uniquely, from the sensed feature or features, the type of the tool attached to the tool holder, the tool holder and the sensor arrangement being such that a tool is electrically isolated from the support when the tool is attached to the tool holder.

20 Preferably the sensor arrangement is operable to sense at least one feature present on a tool in the form of a projection on the tool.

Alternatively the sensor arrangement is operable to sense at least one feature present on a tool in the form of a recess on the tool.

25

Conveniently the sensor arrangement includes a plurality of axially movable rods extending to a face of the tool holder which is adjacent the tool when the tool is attached to the tool holder, there being a respective switch element actuatable in response to movement of each of the rods.

Preferably each rod is resiliently biased to an initial position by means of a spring.

- 5 Advantageously the rods are evenly angularly spaced about the circumference of a notional circle.

Alternatively the rods are arranged in linear co-alignment.

- 10 In a further modified embodiment of the invention the sensor arrangement is operable to sense at least one feature present on the tool in the form of a magnetic element.

- 15 Preferably the sensor arrangement includes a plurality of detectors responsive to a magnetic field.

- 20 Advantageously the tool holder incorporates a connector element to which the tool may be mounted, the connector element being formed of or mounted on an element of insulating material.

- 25 Preferably the processor is adapted to generate an alarm signal if only one said feature on a tool is detected.

The tool holder may be provided in combination with at least one tool.

- 25 Conveniently the tool is provided with two projecting elements positioned to be co-aligned with two said rods.
-

In an alternative embodiment the tool is provided with two recesses positioned to be co-aligned with two said rods.

In a further alternative embodiment the tool is provided with two
5 magnetic elements positioned to be co-aligned with two said detectors.

The tool holder arrangement may be incorporated into a robot.

In order that the present invention may be more readily understood,
10 embodiments thereof will now be described, by way of example, with reference to the accompanying drawings, in which:

FIGURE 1 is a schematic cut-away view of part of an arm provided with a tool holder arrangement in accordance with the invention, and a tool; and
15

FIGURE 2 is a schematic elevational view of a printed circuit board suitable for use with the present invention.

Referring to Figure 1, a tool-receiving end 1 of the arm of a medical
20 robot is shown. The tool-receiving end comprises a housing 2, which is substantially circular in cross section. A substantially circular printed circuit board (PCB) 3 is provided within the housing, the PCB 3 being of slightly smaller radius than the housing 2, and being arranged to be coaxial therewith. The PCB 3 is held in place by suitable mounts 4, which are each attached to an
25 interior surface 5 of the housing 2.

Supported on a front surface 6 of the housing 2 is a substantially cylindrical insulating block 7, which is formed from a substantially electrically non-conducting material. The insulating block 7 is also arranged to be

substantially coaxial with the tool-receiving end 1. Mounted on the insulating block 7, on the opposite side thereof from the tool-receiving end 1, is a connector 8, which is substantially cylindrical (and again coaxial with the tool-receiving end 1), but which has a groove 9 running around the outer circumferential surface 10 thereof. The groove 9 has a flat bottom and the side walls thereof are inclined to the bottom. In an alternative arrangement the connector 8 is of insulating material.

Eight rods 11 are provided, which pass through bores which extend through the connector 8, the insulating block 7 and into the interior of the housing 2. The rods 11 are mounted within respective bores in the connector 8, the insulating block 7 and the housing 2. The bores are parallel and evenly angularly spaced about the circumference of a notional circle. The rods 11 are formed from electrically non-conducting material.

15

Helical springs 12 are provided around portions of each of the rods 11, in enlarged chambers formed at the end of each bore. One end of each spring 12 engages the outer surface 6 of the housing 2, and the other end of each spring 12 engages a flange on the respective rod 11 so that, in a resting position of the spring 12, the rod 11 is held so that a proximal end 13 thereof rests close to the PCB 3. It will be understood that, if any of the rods 11 are pushed inwardly towards the PCB 3, the respective spring 12 will act to oppose this motion, and once the pushing force is removed the spring 12 will return the rod 11 to its resting position.

25

Indentations 14 are provided in the end of the connector 8, the indentations being substantially cylindrical and each being centred around a respective one of the rods 11. The connector 8 is configured so that each

rod 11 protrudes into the space formed by an indentation 14 when in the resting position but does not protrude past a front surface 15 of the connector 8.

The PCB 3 is provided with eight microswitches 16 (as can be seen from Figure 2), which are equi-angularly spaced about the circumference of a notional circle. The arrangement of these microswitches 16 is such that a respective microswitch 16 lies opposite the proximal end 13 of each rod 11 when the rods 11 are in their resting positions. A processor 17 is mounted on the PCB 3, the processor being connected to the microswitches 16.

10

A connecting portion 18 of a surgical tool is also shown in Figure 1. The connecting portion 18 is formed at the end of a shank of the tool. The connecting portion 18 comprises a collar 19 which surrounds a circular recess 20. The recess 20 has a base 21. Provided on the base 21 are two spaced-apart protrusions in the form of axially extending pins 22.

The collar 19 is provided, at diametrically opposed positions, with two radially inwardly directed cylindrical recesses 23, 24. Each recess 23, 24 contains a sliding detent element 25, 26, there being a respective spring 27, 28 between the base of each detent 25, 26 and the base of the respective recess 23, 24. The springs 27, 28 serve to bias the detents 25, 26 radially inwardly. The inwardly protruding end of each detent 25, 26 which extends into the recess 20 has a configuration corresponding to that of the groove 9. The detents 25, 26 may thus form a "snap" coupling with the recess 9, securing the tool which is provided with the connecting portion 18 to the connector 8. A projection (not shown) provided on the connecting portion 18 may engage a key-way (not shown) provided on the connector 8 so that the tool may only be mounted on the connector in a specific predetermined orientation.

Upon releasing the tool from the arm of the medical robot, the springs 12 will remove the rods 11 from engagement with the microswitches 16.

5 It will be appreciated that, with the above-described system, four different tools can be provided, each with a connecting portion 18 as described, but with the two pins 22 on each of the connecting portions 18 being provided in different locations so as to correspond to a different pair of microswitches 16. Ideally, each tool will have pins 21 at locations to correspond to
10 two microswitches 16, neither of which is also associated with any other tool. Hence, either of the two microswitches 16 that are activated when a particular tool is attached to the arm of the medical robot can be used by the processor 17 to identify uniquely the type of the tool. However, if both switches are closed, effectively there is a double confirmation of the identity of the tool.

15

Of course, a greater number of microswitches 16 may be provided on the PCB 3, to accommodate a greater variety of possible tool types.

20 In preferred embodiments of the present invention, an alarm is raised if only one microswitch 16 is activated, or if a combination of two or more microswitches 16 that do not correspond to an individual tool are activated.

25 In the above-described example, the circular arrangement of the microswitches 16 means that the tool must be attached to the arm of the medical robot in a certain predetermined orientation. However, in alternative embodiments, the microswitches 16 are arranged so that, irrespective of the orientation with which the tool is attached to the arm of the medical robot, the tool can be correctly identified. For instance, the microswitches 16 may be arranged in a substantially straight line extending from the centre of the PCB 3

to an edge thereof, with each tool being provided with two concentric rings of pins, similar to the pins 22, on the base 21 of the recess 20. The distance of each of the rings or pins from the centre of the base 21 indicates which type of tool it is, and clearly microswitches 16 at certain distances from the centre of the PCB 3 will be activated when this system is employed, irrespective of the relative orientations of the tool and arm.

In an alternative embodiment of the present invention, each tool may be provided with indentations, rather than pins 22, in the base 21 of the recess 20 thereof. In this embodiment, the ends of the rods 11 may protrude past the forward-facing surface 15 of the connector 8, and it will be understood that the tool can then be identified from a combination of two microswitches 16 that are not activated when the tool is connected to the arm of the medical robot.

It is also envisaged that the present invention may operate by the presence of one or more magnets on the tool, with the connecting portion 18 of the arm of the medical robot being provided with a number of magnetic detectors. When the tool and the arm are connected to one another the magnetic detectors such as Hall effect switches or magnetic reed switches will lie directly opposite the magnets and will be able to detect the presence thereof.

It will be understood that a preferred embodiment of the present invention provides a reliable system of uniquely identifying tools attached to the arm of a medical robot, while maintaining electrical insulation between the tool and the arm, and which alleviates many difficulties associated with the prior art.

In the present Specification "comprises" means "includes or consists of" and "comprising" means "including or consisting of".

The features disclosed in the foregoing description, or the following Claims, or the accompanying drawings, expressed in their specific forms or in terms of a means for performing the disclosed function, or a method or process 5 for attaining the disclosed result, as appropriate, may, separately, or in any combination of such features, be utilised for realising the invention in diverse forms thereof.

CLAIMS:

- 5 1. A tool holder arrangement including:
 a tool holder to be mounted on a support and allowing removable
 attachment thereto of any one of a plurality of tools;
 a sensor arrangement operable to sense at least one feature present on a
 tool when attached to the tool holder, being a feature or features unique to the
10 specific tool; and
 a processor operable to identify uniquely, from the sensed feature or
 features, the type of the tool attached to the tool holder,
 the tool holder and the sensor arrangement being such that a tool is
 electrically isolated from the support when the tool is attached to the tool
15 holder.
2. A tool holder arrangement according to Claim 1 wherein the sensor
 arrangement is operable to sense at least one feature present on a tool in the
 form of a projection on the tool.
- 20 3. A tool holder arrangement according to Claim 1 wherein the sensor
 arrangement is operable to sense at least one feature present on a tool in the
 form of a recess on the tool.
- 25 4. A tool holder arrangement according to Claim 2 or Claim 3 wherein the
 sensor arrangement includes a plurality of axially movable rods extending to a
 face of the tool holder which is adjacent the tool when the tool is attached to the
 tool holder, there being a respective switch element actuatable in response to
 movement of each of the rods.
-

5. A tool holder arrangement according to Claim 4 wherein each rod is resiliently biased to an initial position by means of a spring.

5 6. A tool holder arrangement according to Claim 4 or 5 wherein the rods are evenly angularly spaced about the circumference of a notional circle.

7. A tool holder arrangement according to Claim 4 or 5 wherein the rods are arranged in linear co-alignment.

10

8. A tool holder arrangement according to Claim 2 or 3 wherein the sensor arrangement is operable to sense at least one feature present on the tool in the form of a magnetic element.

15 9. A tool holder arrangement according to Claim 8 wherein the sensor arrangement includes a plurality of detectors responsive to a magnetic field.

10. A tool holder arrangement according to any one of the preceding claims wherein the tool holder incorporates a connector element to which the tool may
20 be mounted, the connector element being formed of or mounted on an element of insulating material.

11. A tool holder arrangement according to any one of the preceding claims wherein the sensor arrangement is operable to sense two said features on a tool.

25

12. A tool holder arrangement according to Claim 11 wherein the processor is adapted to generate an alarm signal if only one said feature on a tool is detected.

13. A tool holder according to any one of the preceding claims in combination with at least one tool.

5 14. A tool holder arrangement according to Claim 13 as dependent upon Claim 2 and 3 wherein the tool is provided with two projecting elements positioned to be co-aligned with two said rods.

10 15. A tool holder arrangement according to Claim 13 as dependent on Claims 2 and 4 wherein the tool is provided with two recesses positioned to be co-aligned with two said rods.

15 16. A tool holder arrangement according to Claim 13 as dependent upon Claim 9 wherein the tool is provided with two magnetic elements positioned to be co-aligned with two said detectors.

17. A tool holder arrangement including:

a tool holder to be mounted on a support and allowing removable attachment thereto of any one of the plurality of tools;

20 a sensor arrangement operable to sense two features present on a tool when attached to the tool holder, being features unique to the specific tool; and

a processor operable to identify uniquely, from the sensed features, the type of tool attached to the tool holder,

25 the tool holder and the sensor arrangement being such that the tool is electrically isolated from the support when the tool is attached to the tool holder.

18. A tool holder arrangement according to any one of the preceding claims incorporated in a robot.

19. A tool holder arrangement substantially as herein described with reference to and as shown in the accompanying drawings.

5 20. A tool holder arrangement substantially as hereinbefore described with reference to and as shown in the accompanying drawings in combination with at least one tool.

21. Any novel feature or combination of features disclosed herein.

10

15

20


25

ABSTRACT

5 **“A Tool Holder Arrangement”**

A tool identification system, comprising: a tool holder allowing removable attachment thereto of any one of a plurality of tools; a sensor arrangement
10 operable to sense features present on a tool attached to the tool holder; a processor operable to identify uniquely, from the sensed features, the type of the tool attached to the tool holder; and an insulation arrangement provided between the tool holder and the sensor arrangement, thereby electrically insulating the tool holder from the sensor arrangement.

15






FIG 1




FIG 2